

Product Specification

Product Class: LED LENS

ItemNo: **DK-14-100x65-TP-IV-M**


Material: PC (UV)

Certification: RoHS




Content

Specification-----	3
2D Drawing-----	4
Optical Datasheet-----	5
Packing-----	6
Application Notes-----	7

Specification

Item No	Picture	Size	Matched LED	Lighting Application
DK-14-100X65-TP-IV-M		Diameter: 13.9*13.9mm Height:6.54mm FWHM:100X65°	3535	Streetlight

Drawing



Optical Test Report


产品特征

灯具制造厂商:	
电压: 34.0 V	电流: 0.222 A
功率: 7.54 W	功率因数: 1.000


光度结果

灯具CIE分类: 直接型	额定光通量: 854.4 lm
灯具光通量: 854.4 lm	灯具效率: 100%
下射光通量比: 96%	上射光通量比: 4%
水平扩散角 (10%, 50%, 75%, 100%): H146.2, H119.3, H92.8, H58	
垂直扩散角 (10%, 50%, 75%, 100%): V174.1, V89.8, V75.6, V62	
灯具光效等级 (LER): 113.36	中心光强: 181.71 cd
峰值光强: 403 cd	峰值光强位置: H90 V62
S/MH(C0/C180): 1.62	S/MH(C90/C270): 1.66


灯具实物照片



配光曲线



配光曲线



Packing

Packing Material	Packing Materil size	Packing Specification
Vacuum bag	260*380 mm	1000pcs/bag
Outer box	330*255*255 mm	

Application Notes

- (1) Please use a little water and soft fabric (air-laid paper) to clean the product if necessary.
- (2) Forbid to use industrial solvent to clean the product, such as alcohol.
- (3) The working temperature is $-35^{\circ}\text{C}\sim+120^{\circ}\text{C}$.
- (4) Storage environment temperature is $0^{\circ}\text{C}\sim40^{\circ}\text{C}$, humidity is 30%~95%.
- (5) The product has the function to change the ray of light, it is made of optical material, the effect shall be influenced once pollute. Please do not open the packing before use it, to avoid the dust pollution.
- (6) Protect the product from the sun and other ultraviolet ray, as these will lead to aging, change color, crack, etc.
- (7) Please wear gloves once install the product, avoid to abrasion the product surface.
- (8) Forbid to use acidic or alkaline solution touch the product, avoid to generate the chemical reactions.