

## EUP50M-1WMC-0 (Product No.:101100032101)

### Summary

EUP50M-1WMC-0 is a 50W AC/DC constant current mode output LED driver featuring the multiple levels selectable by DIP switch and complies with DMX512(1990). EUP50D-1WMC-0 can be connected to DMX main controller or RDM controller to achieve a smooth dimming effect.

### Product Features

- Single channel output, output current level selectable by DIP S.W.
- Meet DMX512(1990)
- Support RDM function
- Wide input voltage of 100VAC ~ 240VAC
- High efficiency up to 88%
- Built-in active PFC function
- Dimming effect smooth, no flicker
- Protections: over load, short circuit
- Suitable for indoor LED lighting application, such as down light, panel light, and so on



### Application



Downlight



Panel Light



Spotlight



Ceiling Light



Decorative Light



Floor Light





Flood Light

### Technical Parameters

| Model      | EUP50M-1WMC-0                      |                                                                                                                                                      |
|------------|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------|
| Input      | Efficiency                         | 88%@230VAC,full load                                                                                                                                 |
|            | Voltage                            | 100VAC-240VAC                                                                                                                                        |
|            | Frequency Range(Hz)                | 50/60Hz                                                                                                                                              |
|            | Power Factor                       | ≥0.9@230VAC,75%-100% load                                                                                                                            |
|            | Current                            | 0.26Amax@230VAC                                                                                                                                      |
|            | THD                                | <10%@230VAC,full load                                                                                                                                |
|            | Inrush current                     | Cold start,30A[twidth=22us measured at 50% Ipeak] @230VAC                                                                                            |
| Output     | Current(mA) Voltage (VDC) Power(W) | 500mA/9-65V/32.5W 650mA/9-65V/42.2W 700mA/9-65V/45.5W 850mA/9-59V/49.3W<br>1000mA/9-50V/50W *850mA/9-59V/49.3W 1050mA/9-48V/50.4W 1200mA/9-42V/50.4W |
|            | Channel                            | 1                                                                                                                                                    |
|            | Current Tolerance                  | ±5% (500mA +7%, 650mA +10%, *850mA +7%)                                                                                                              |
|            | Max Output Voltage                 | 90VDC                                                                                                                                                |
|            | Output LF current ripple(< 120 Hz) | < 3%                                                                                                                                                 |
| Function   | Dimming Mode                       | DMX512 dimming                                                                                                                                       |
| Protection | Over load                          | Hiccup, recovers automatically after fault removed                                                                                                   |
|            | Short circuit                      | Shut down the output, recovers automatically after fault removed                                                                                     |
| Others     | Working Temp.                      | -20°C~50°C                                                                                                                                           |
|            | Storage Temp., Humidity            | -40°C~85°C, 20-90%RH                                                                                                                                 |
|            | tc                                 | 95°C                                                                                                                                                 |
|            | Material                           | Metal                                                                                                                                                |
|            | IP Rating                          | IP20                                                                                                                                                 |
|            | Lifetime                           | 30,000h@tc:95°C                                                                                                                                      |
|            | Warranty Condition                 | 3 years                                                                                                                                              |
|            | Switch Cycle                       | >15,000 times                                                                                                                                        |
|            | Packing(weight)                    | Net weight: 225g±5%/PCS; 50PCS/Carton;11.75kg±5%/Carton; Carton Size: 517*337*179mm(L*W*H)                                                           |
|            | Dimension                          | 137*82*31mm(L*W*H)                                                                                                                                   |

### Dimension(mm)



The diagram illustrates the RDM Controller system components and their connections:


- PC**: Connected to the RDM Controller via a standard Ethernet cable.
- RDM Controller**: A blue device with a USB port, an Ethernet port, and a power input. It is connected to the LED strip via a 4-pin ribbon cable.
- LED Strip**: A white strip with red and green LEDs. It is connected to the RDM Controller and a light fixture.
- Light**: A black, cylindrical light fixture connected to the LED strip.
- Input 100-240VAC**: A power cord connected to the LED strip.

The LED strip is labeled with the following specifications:


- DMX/RDM Constant Current Dimming Driver
- EUPHOM-1WMC-0
- Us:100-240V~ 50/60Hz in 2.0Amax@220V~
- Us:50Vmax im: Pwr:50Wmax PF>0.9
- ta:20°C~+50°C ta@Tc
- For LED modules only
- 1011000032101
- CE, SELV, and other safety markings.

|    |     |                |                 |                 |                 |  |
|----|-----|----------------|-----------------|-----------------|-----------------|--|
| ON | OFF | 1 2 3          |                 |                 |                 |  |
|    |     | 500mA<br>9-65V | 700mA<br>9-65V  | 850mA<br>9-59V  | 1050mA<br>9-48V |  |
| ON | OFF |                |                 |                 |                 |  |
|    |     | 650mA<br>9-65V | *850mA<br>9-59V | 1000mA<br>9-50V | 1200mA<br>9-42V |  |

### Dimming Curve



### Derating Curve



| Load (%) | 230Vac Efficiency (%) | 100Vac Efficiency (%) |
|----------|-----------------------|-----------------------|
| 60       | 84.8                  | 85.1                  |
| 70       | 86.3                  | 86.0                  |
| 80       | 87.0                  | 86.5                  |
| 90       | 87.8                  | 87.1                  |
| 100      | 88.8                  | 87.7                  |

| Load% | 230Vac PF | 100Vac PF |
|-------|-----------|-----------|
| 60%   | 0.925     | 0.995     |
| 70%   | 0.940     | 0.998     |
| 80%   | 0.950     | 0.998     |
| 90%   | 0.955     | 0.998     |
| 100%  | 0.965     | 0.998     |

1. The product shall be installed and serviced by a qualified person.
2. This product is non-waterproof. Please avoid the sun and rain. When installed outdoors please ensure it is mounted in a water proof enclosure.
3. Good heat dissipation will prolong the working life of the controller. Please ensure good ventilation.
4. Please check if the output voltage and current of any LED power supplies used comply with the requirement of the product.
5. Please ensure that adequate sized cable is used from the controller to the LED lights to carry the current. Please also ensure that the cable is secured tightly in the connector.
6. For safety consideration, PVC or rubber cord of 0.75-2.5mm<sup>2</sup> is recommended for input and output terminal(s) (excluding signal terminals). Flat power cord is not suitable. Ensure all wire connections and polarities are correct before applying power to avoid any damages to the LED lights.
7. If a fault occurs please return the product to your supplier. Do not attempt to fix this product by yourself.

User's manual: 2019-9

EUP50M-1WMC-0 (产品代码:101100032101)

概述

EUP50M-1WMC-0 是一款可以提供 500/650/700/850/1000/1050/1200mA 7 档电流的 LED 驱动器。输出电流可以通过DIP 拨码开关简易设置，可以通过 DMX 主控或 RDM 主控实现平滑的调光效果。

产品特点

- 单通道恒流输出，多级电流可选
- 遵循标准 DMX512(1990)
- 支持 RDM 写码功能
- 宽电压输入：100VAC ~ 240VAC
- 效率高达 88%
- 内建主动式 PFC 功能
- 过载保护，短路保护
- 适用于 LED 室内灯具,比如筒灯，面板灯等



应用



筒灯



面板灯



射灯



吸顶灯



装饰灯



落地灯





投光灯


技术参数

| 型号 | EUP50M-1WMC-0   |                                                                          |                    |                    |
|----|-----------------|--------------------------------------------------------------------------|--------------------|--------------------|
| 输入 | 效率              | 88%@230VAC，满载                                                            |                    |                    |
|    | 电压              | 100VAC-240VAC                                                            |                    |                    |
|    | 频率              | 50/60Hz                                                                  |                    |                    |
|    | 电流              | 0.26Amax@230VAC                                                          |                    |                    |
|    | THD             | <10%@230VAC，满载                                                           |                    |                    |
|    | 功率因素            | ≥0.9@230VAC，75%-100%负载                                                   |                    |                    |
|    | 浪涌电流            | 冷启动 30A[在 50%Ipeak 下测试 twidth=22us]@230VAC                               |                    |                    |
| 输出 | 电流/电压/功率        | 500mA/9-65V/32.5W                                                        | 650mA/9-65V/42.2W  | 700mA/9-65V/45.5W  |
|    |                 | 1000mA/9-50V/50W                                                         | *850mA/9-59V/49.3W | 1050mA/9-48V/50.4W |
|    | 通道              | 1                                                                        |                    |                    |
|    | 电流精度            | ±5% (500mA +7%, 650mA +10%, *850mA +7%)                                  |                    |                    |
|    | 最大输出电压          | 90VDC                                                                    |                    |                    |
| 功能 | 低频电流纹波 (<120Hz) | <3%                                                                      |                    |                    |
|    | 调光方式            | DMX512/RDM                                                               |                    |                    |
| 保护 | 过载保护            | 打嗝，故障去除后自恢复                                                              |                    |                    |
|    | 短路保护            | 关断输出，故障去除自恢复                                                             |                    |                    |
| 其它 | 工作温度            | -20℃~50℃                                                                 |                    |                    |
|    | 储存温度、湿度         | -40℃~85℃, 20-90%RH                                                       |                    |                    |
|    | tc              | 95℃                                                                      |                    |                    |
|    | 材质              | PC                                                                       |                    |                    |
|    | 防水等级            | IP20                                                                     |                    |                    |
|    | 寿命              | 30,000小时@tc:95℃                                                          |                    |                    |
|    | 质保              | 3年                                                                       |                    |                    |
|    | 开关周期            | >15,000次                                                                 |                    |                    |
|    | 包装尺寸(重量)        | 净重: 225g±5%/PCS; 50PCS/Cartron; 11.75kg±5%/箱; 外箱尺寸: 517*337*179mm[长*宽*高] |                    |                    |
|    | 尺寸              | 137*82*31mm (长*宽*高)                                                      |                    |                    |

尺寸(mm)



接线图




电流选择表


| ON | OFF | 1     | 2      | 3      | 4      | 5 | 6 | 7 | 8 | 9 | 10 |
|----|-----|-------|--------|--------|--------|---|---|---|---|---|----|
|    |     | 500mA | 700mA  | 850mA  | 1050mA |   |   |   |   |   |    |
|    |     | 9-65V | 9-65V  | 9-59V  | 9-48V  |   |   |   |   |   |    |
| ON | OFF | 1     | 2      | 3      | 4      | 5 | 6 | 7 | 8 | 9 | 10 |
|    |     | 650mA | *850mA | 1000mA | 1200mA |   |   |   |   |   |    |
|    |     | 9-65V | 9-59V  | 9-50V  | 9-42V  |   |   |   |   |   |    |

备注：出厂默认设置电流为500mA(1,2,3在OFF状态)


调光曲线




降额曲线



效率 VS 负载



PF VS 负载



注意事项:

- 1、本产品请由具有专业资格的人员进行调试安装。
- 2、本产品不能防水，需避免日晒雨淋，如安装在户外，请用防水箱。
- 3、良好的散热条件会延长产品的使用寿命，请把产品安装在通风良好的环境。
- 4、请检查使用的LED电源输出电压电流，是否符合产品要求。
- 5、出于安全考虑，推荐输入和输出（信号端除外）用0.75-2.5mm<sup>2</sup>PVC或橡胶线缆，并确保接线牢固，以免电线过热或接触不良触发事故。扁平电源线不适用。
- 6、通电调试前，应确保所有接线正确，以避免因接线错误而导致灯具损坏。
- 7、如果发生故障，请勿私自维修；如有疑问，请联系供应商。

※ 本说明书内容如有更新，恕不另行通知。若您使用的产品功能与说明书不一致时，请以产品为准。如有疑问请与我们联系。