



Features:

- IP 65 protection constant current LED driver
- Non-isolated and bipolar no flicker
- Adjustable current with external potentiometer
- Input surge protection up to 6/6KV
- Low residual voltage output protection function
- Optional for 0-10V/PWM/resistance dimming
- 12V auxiliary power device
- Dip-switch for wattage change and dip-switch for CCT change.
- Application: industrial and mining lamps
- Afterglow removing function
- 5 years warranty

SPECIFICATION

5YEAR
WARRANTY

UL
LISTED
E478128

FC

CE

Article Item	Maximum Output Wattage(W)	IP Protection Grade	Input Voltage(V)	Output Voltage(V)	Output Current(mA)	Input Surge Protection	Size (L*W*H) mm
BQ-100H-260-Z	100	die-casting shell IP65	120-347	180-260	350-500	6/6KV	φ128*61.5
BQ-120H-260-Z	120	die-casting shell IP65	120-347	180-260	400-600	6/6KV	φ128*61.5
BQ-150H-260-Z	150	die-casting shell IP65	120-347	180-260	500-750	6/6KV	φ128*61.5
BQ-200H-260-Z	200	die-casting shell IP65	120-347	180-260	700-1000	6/6KV	φ128*61.5
BQ-240H-260-Z	240	die-casting shell IP65	120-347	180-260	850-1200	6/6KV	φ128*61.5
BQ-300H-260-Z	300	die-casting shell IP65	120-347	180-260	1000-1500	6/6KV	φ150*61.5