

DATASHEET

S01.01.02.385_DARWIN-15x55

Architecture Lighting:

~15x55° beam with holder.

D23.22 mm for up to 3535 size LED packages.


1.General Information

Lens Material	: PMMA
Holder Material	: PC
Size	: D23.22mm
typ.FWHM	: 15x55°
Design LED	: CREE XPE
Compatibility	: 2835/3030/3535
typ.Efficiency	: 93%
Fasten	: Glue+Frame
IP class	: N/A
Zhaga	: N/A
RoHS	: YES
Color	: Clear



2.MECHANICAL SPECIFICATION

UNIT:mm



Dimensions with unmarked tolerances refer to GBT14486 tolerance table.

3. OPTICAL RESULTS


1) PHOTOMETRIC DATA(MEASURED):



LED model CREE XPE
Light colour White
LEDs/each optic 1
FWHM : H46.6°,V14.9°
FWTM : H76.4°,V44.1°

Required components:

N/A




2) PHOTOMETRIC DATA(MEASURED):



LED model OSRAM 3030
Light colour White
LEDs/each optic 1
FWHM : H53.8°,V16.0°
FWTM : H81.4°,V44.2°

Required components:

N/A



4.Usage and Maintenance

- 1) If necessary, clean lenses with mild soap, water and soft cloth.
- 2) Never use any commercial cleaning solvents on lenses, like alcohol.
- 3) Please handle lens with wearing gloves, skin oils may damage lens or its optical characteristic.

5.Note

Please test the data again before using. The chart data is for reference only.

The appearance and specifications of the product can be changed to improve the quality and/or performance without notice.

Last update:2024/8/21

SUNLUMIN OPTICS CO.,LTD

2nd Floor, Building D, No.56 Liuhe Road, Tangkeng Community,
Henggang Street, Longgang District, Shenzhen

E
info@sunlumin-optics.com

www.
sunlumin-optics.com